

Small Flood

HPS / 35 - 100 watts

MH / 50 - 100 watts

Application

Great for lighting building facades, displays, signs, or for general security lighting purposes



Features

- Die-cast housing with hinged door frame for easy relamping (lamp included)
- Textured bronze finish with tempered glass lens
- 1/2" adjustable knuckle
- UL listed for wet locations




FLOODS

DIMENSIONS




MOUNTING DETAIL



Fits 1/2" NPT

PHOTOMETRICS

175W MH @ 15' Mounting Height
and aimed 30° Below Horizontal
Isofootcandles



ORDERING INFORMATION

Catalog #	Watts	Volts	HI Ballast Model #	Ballast	ANSI	Lamp Part #
SFL-35-HPS-120	35 HPS	120	S0035-02C-111-E	R-NPF	S76	LU35/MED
SFL-50-HPS-120	50 HPS	120	S0050-02C-111-E	R-NPF	S68	LU50/MED
SFL-70-HPS-120	70 HPS	120	S0070-02C-111-E	R-NPF	S62	LU70/MED
SFL-100-HPS-120	100 HPS	120	S0100-02C-111-E	R-NPF	S54	LU100/MED
SFL-50-MH-2T	50 MH	2T	M0050-23C-511-DE	HX-HPF	M110	MH50/U/MED
SFL-70-MH-4T	70 MH	4T	M0070-71C-511-DE	HX-HPF	M98	MH70/U/MED
SFL-100-MH-4T	100 MH	4T	M0100-71C-511-DE	HX-HPF	M90	MH100/U/MED

ACCESSORIES

Catalog #	Description
SFLWG	Wire guard with stainless steel construction
SFLGS	Black powder-coat finished glare shield that can be reverse mounted to use as a back cutoff
SFLVG	Clear polycarbonate vandal guard
FLPTF	Textured bronzed finished die-cast aluminum post top fitter with three 1/2" tapped holes and coin plugs (fits 3" to 3-1/2" pipe)
FLGSTK	HID ground stake with position adjustable stabilizer, die-cast fitting that accepts 1/2" knuckle, and built in wiring compartment

• Specifications are subject to change without notice.

HOWARD[®]
LIGHTING PRODUCTS

Lighting for life.

www.HowardLightingProducts.com • 800.956.3456 • 601.422.1652 (fax)